

DEKOR-WACHS LASUR

Waxy Decorative Finishing Lasur



Ready to use high performing flexible finishing lasur for outdoor surfaces. The product penetrates into the wood enhancing the grain and providing a soft, polished finish. The high-quality substances and UV filters in the product prevent the formation of dye rots and attacks by insects like woodworm, while guaranteeing optimal resistance to weather conditions. Its high density facilitates brush application, even on vertical supports.

- High Solid non-peeling finish
- Based on natural wax, oils and resin
- UV-filters
- Protects against molds and rots
- Prevents oxidation and weathering
- Full pigmented
- Light resistant colors
- No dripping
- Brush application
- Indoor and outdoor use

Used as a finishing lasur over Holz Lasur color primer.

Also used alone, as a self-sealer.

Apply all along the wood grain.

Apply two-three coats.

Wait 6-8 hrs between consecutive coats.

Wait 24 hrs for complete drying.

To increase smooth effect, sand the surface, sandpaper grit 220-240.

Cod.	Cap.	Pcs.
3320XX-DEC	750 ml	06 pcs.
3322XX-DEC	2,5 Lt	02 pcs.
3330XX-DEC	5 Lt	02 pcs.
3344XX-DEC	10 Lt	
3340XX-DEC	20 Lt	

NATURAQUA DEKOR-WACHS LASUR

Waxy Decorative Finishing Lasur - Water based



Ultimate generation waterborne finishing lasur, formulated with waxes and resins resistant to sunlight and weathering. Excellent coverage and wetting of the surface, extremely easy application. With addition of UV-filters, it is suitable for every kind of wooden surface, and it is perfect to treat shutters, fences, balconies where a covering and uniform color is required.

- High solid finish.
- Water-based.
- High quality resins.
- UV-filters.
- Protects against molds.
- Prevents from weathering.
- Full pigmented.
- Light resistant colors.
- No dripping.
- Brush or spray application.
- Indoor and outdoor use.

Used as a finishing lasur over Holz Lasur color primer.

Also used alone as self sealer (dilute first coat 20% water).

Apply all along the wood grain.

Apply two-three coats.

Wait 6-8 hrs between consecutive coats.

Wait 24 hrs for complete drying.

To increase smooth effect, sand the surface, sandpaper grit 220-240.

Cod.	Cap.	Pcs.
NAT3320XX-DEC	750 ml	06 pcs.
NAT3322XX-DEC	2,5 Lt	02 pcs.
NAT3330XX-DEC	5 Lt	02 pcs.
NAT3344XX-DEC	10 Lt	
NAT3340XX-DEC	20 Lt	



BORMA WACHS®

Wood Professional Cosmetics



B.P.S. s.r.l.

Via E. Fermi, 17 - 30020 Torre di Mosto - Venezia Italy

Tel. +39 0421 951900 - Fax +39 0421 951902

www.bormawachs.com



DEKOR-WACHS LASUR

Color Chart

DEKOR-WACHS LASUR

Waxy Decorative Finishing Lasur



 Sage green 133	 Pine green 136	 115 Cream	 Beech 42	 Birch 06
 Orange Orchid 122	 Red poppy 125	 Dark Blue 140	 Ice Grey 100	 Light Olive Green 81
 Turtledove 116	 Sun yellow 120	 Mahogany red 128	 Chocolate 59	 Dark Chocolate 63

NATURAQUA DEKOR-WACHS LASUR

Waxy Decorative Finishing Lasur - Water based



 Sage green 133	 Pine green 136	 115 Cream	 Beech 42	 Birch 06
 Orange Orchid 122	 Red poppy 125	 Dark Blue 140	 Ice Grey 100	 Light Olive Green 81
 Turtledove 116	 Sun yellow 120	 Mahogany red 128	 Chocolate 59	 Dark Chocolate 63

